

NOTES:



1. THIS DRAWING DEFINES THE OVERALL GEOMETRY AND PERFORMANCE SPECIFICATIONS OF THE PART/ASSEMBLY, AND CONSTITUTES THE ACCEPTANCE CRITERIA THEREOF. CONFORMANCE OF HARDWARE TO THESE REQUIREMENTS IS ACCEPTABLE IN LIEU OF VENDOR DOCUMENTATION.

2. SUGGESTED MFR'R: DFCI SOLUTIONS INC.
425 UNION BLVD
WEST ISLIP, NY 11795


SUGGESTED MFR'R: SOUTHCO
210 N. BRINTONLAKE RD.
CONCORDVILLE, PA.19331
(610)459-4000

SHEET	REV	ECO	DATE	DESCRIPTION	BY	APR	CHK
1	N/C	1	04/28/2011	MFR WAS DFS, ORLANDO FLA OBSOLETE DZUS P/N REPLACED BY CURRENT DFCI P/N, FINISH WAS TYPE II	REB	REB	LS
1	A		07/15/2021	ADDED SOUTHCO MFG AND -2	DT	ZA	RL

ENGR. STD. P/N	MFR'R	MFR'R P/N	DESCRIPTION
ES34160-1	DFCI	1219-3175-Z3CT (RoHS COMPLIANT)	SIZE 3 RECEPTACLE; ALT. P/N 1219-3175-Z3YT (YELLOW CHROMATE) ACCEPTABLE ALT. P/N 1219-3175-Z3Y (YELLOW CHROMATE) ACCEPTABLE
ES34160-2	SOUTHCO ALT: DFCI	D4-R35CBCNA	SIZE 3.5 RECEPTACLE; ALT. P/N 2350-18-C3C, D4-R35, 2350-18-Z3CT, D4-R35ZCTNA

-1 RECEPTACLE

MATERIAL: MUSIC WIRE PER ASTM A228
FINISH: 0.0003 IN THICK ZINC TRIVALENT CLEAR,
TRIVALENT CHROMATE CLEAR PER ASTM-B-633,
TYPE III, SC 2

-2 RECEPTACLE

MATERIAL:

CAP: 1008/1010 STEEL PER ASTM A109/A109M

SPRING/PIN: MUSIC WIRE PER ASTM A228

BASE: 4130 STEEL

FINISH: CADMIUM ELECTROPLATED .0003 THICK, CLEAR CHROMATE PER
QQ-P-416, TYPE 1, CLASS 2, CLEAR.

ALT FINISH: 0.0003 IN THICK ZINC TRIVALENT CLEAR, TRIVALENT
CHROMATE CLEAR PER ASTM-B-633, TYPE III, SC 2

BREAK ALL SHARP EDGES

Paravion® Inc. Technology		TITLE RECEPTACLE, DZUS FASTENER		DRAWING NO. ES34160	
DIMENSIONS IN INCHES		DRAWN BY	APRVD. BY	CHK'D BY	DATE
TOLERANCES EXCEPT WHERE NOTED:		MR	MR	LS	02/27/01
PROTO		ECO			
N/C		DO NOT SCALE DRAWING			SHEET 1 OF 1
		© 2021 PARAVION TECH., INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY, INC.			

.X = ± .1

.XX = ± .05

.XXX = ± .010

ANGLES = ± 1°